



1. CUT CEILING TILE OPENING 10-1/4" X 10-7/8"  
(NOTE : FOR DRYWALL CEILING MOUNT FIXTURE TO CEILING STRUCTURE BEFORE DRY WALLING)
2. POSITION FIXTURE IN CEILING AND SECURE MOUNTING CHANNELS TO TEE RAIL WITH (4) SCREWS PROVIDED (NOTE LAMP SIDE OF FIXTURE AWAY FROM WALL)
3. COMPLETE WIRING TO POWER SUPPLY AND GROUND BY UTILIZING THE ACCESS PLATE
4. INSTALL ACCESS PLATE TO TOP OF HOUSING
5. LIFT FIXTURE THRU FRAME OPENING ORIENT LAMP SIDE AWAY FROM WALL, ENGAGE TORSION SPRINGS AND PUSH INTO CEILING

065122

**Hg** MARK MEANS LAMP CONTAINS MERCURY.

FOLLOW DISPOSAL LAWS.

SEE [WWW.LAMPRECYCLE.ORG](http://WWW.LAMPRECYCLE.ORG)

 <b>JUNO LIGHTING GROUP</b>		12001 Exit Five Pkwy Fishers, IN 46037		
		 <b>SQUARE D</b>		
<b>1' X 1' WALL WASH INSTALLATION</b> INSTRUCTION SHEET				
PROJECT	NONE	DRAWN	MDW	DWG. NO.
SCALE	NTS	REV	DATE	11/02/94
				11649