

ACCUFLOOD
EF SERIES

AccuLite™

Product Features:

- Compact size, EPA 1.12 ft² (with 1.2 drag factor)
- Full range of lamps up to 400W metal halide and high pressure sodium
- Available with either slipfitter or yoke
- Removable hinged door



Applications

- AccuFlood™ 'EF', a compact floodlight designed for use with metal halide and high pressure sodium lamps
- An ideal choice for both commercial and residential complexes or larger industrial areas

Features

Compact The compact size of the 'EF' floodlight allows the use of lighter poles or more fixtures per pole for significant overall project cost savings

Full Lamp Choice AccuFlood™ 'EF' is suitable for lamps from 70W HPS, 175W MH to 400W

- Available with the choice of slipfitter or yoke mounting

Construction AccuFlood™ 'EF' features a gasketed (not siliconed) lens

- The lens assembly and fixture body feature durable high temperature silicone rubber gaskets

- Heavy duty die cast one piece lens and body features an attractive architectural soft edge profile
- The hinged cover assembly is keyed to prevent accidental removal during relamping

Lampholder Specification grade porcelain, mogul base

Optical Assembly Wide beam distribution pattern for maximum lighting performance

Ballasts A full range of ballasts is available

- HPF ballasts for low temperature starting
- PS -40°C, MH -30°C, HPS -40°C

Finish 'EF' floodlights are finished in a dark bronze polyester powder coat finish with excellent corrosion resistant characteristics

Certification UL, cUL, Wet location rated

Ordering Information with Electro-Magnetic Ballast

EF Series	-400MH Lamp	-QT Ballast	-SF Mounting	-PC Options
EF	Pulse Start Metal Halide Mogul base - 70PS 70W ED28 - 100PS 100W ED28 - 150PS 150W ED28 - 175PS 175W ED28 - 200PS 200W ED28 - 250PS 250W ED28 - 320PS 320W ED28 - 350PS 350W ED28 - 400PS 400W ED28	Electromagnetic - QT 120V, 208V, 240V, 277V - TT 120V, 277V, 347V -480 480V∇	Yoke (Trunnion) No suffix Yoke mount Slipfitter -SF Fits 2" IPS 2-3/8" O.D. tenon	Lamp - L Clear Lamp Photocontrol - PC Indicate voltage to be used on multi-tap ballast Available 120, 208, 240, 277 & 347V Photocontrol Receptacle - PCR 480V receptacle only. Photocontrol by others Fuse Holder - F1 Single pole Supplied with fuse Indicate voltage on Quad-Tap and Tri-Tap ballasts
	Probe Start Metal Halide Mogul base - 175MH 175W ED28 - 250MH 250W ED28 - 400MH 400W ED28			
	High Pressure Sodium Mogul base - 70HP 70W ED23.5 - 100HP 100W ED23.5 - 150HP 150W ED23.5 - 250HP 250W ED18 - 400HP 400W ED18			

Accessories


Catalog No.	Description
EF-TA	Tenon Adapter, converts yoke to slipfitter For 2" IPS (2 3/8" OD) tenons
EF-CA	Cross Arm Adapter, for yoke mount horizontal aiming
EF-LS	Vandal Shield, lexan®
EF-TV	Top Visor
WB1-BZ	Wall Bracket, for slipfitter mounted luminaires

MUST BE ORDERED SEPARATELY.

Photometrics


EF400MH-volts

NEMA 7H X 7V LSC CB773
400 watt clear MH, 33,100 lumens
Mounting Height: 20' Aimed: 60°




EF400MH-volts

NEMA 7H X 7V LSC CB774
400 watt clear HPS, 50,000 lumens
Mounting Height: 20' Aimed: 60°





Slipfitter Mount

EPA: 1.12 ft²
(Includes 1.2 drag factor)



Yoke Mount

EPA: 1.12 ft²
(Includes 1.2 drag factor)



WB1-BZ

Mounting: 2 holes 7/16" dia.
Tenon: 2" IPS (2-3/8" od)

USA 1300 S. Wolf Road • P.O. Box 5065, • Des Plaines, IL 60017-5065
AccuLite Customer Service • PHONE 847.827.9880 • FAX 847.827.2457 • junolightinggroup.com

Canada 220 Chrysler Drive • Brampton, ON • Canada L6S 6B6 • PHONE 905.792.7335 • FAX 905.792.0064
219 Shoemaker Street • Kitchener, ON • Canada N2E 3B3 • PHONE 800.265.7844 • FAX 800.594.5173

Regional Offices & Warehouses: Atlanta, Dallas, Los Angeles, Philadelphia, Toronto

LIT-ACCU-EF



AccuLite is a registered trademarks of Juno Lighting, Inc.
Specifications subject to change without notice.
© 2007 JUNO LIGHTING GROUP

