

4" Sq. T-4 Metal Halide Downlight

Designer Series



Description

Two-piece optical system maximizes lamp output while providing excellent glare control.

Features

Upper Reflector Faceted, specular clear Alzak® reflector is standard

Lower Trim Self-flanged, clear Alzak® (SATSF) satin trim with low iridescent finish is standard • Other Alzak® satin finishes are available; see options

Electrical Ballast: 120/277V electronic solid state, HPF, reliable starting to -30° • Pre-wired junction box, thermal protection and 200° C, SF-1 wire standard
• Lamp holder: G8.5 bi-pin socket base with recessed female contacts, 1A, 750V, rated for 5kV pulse

Mechanical Fixture housing is cold rolled steel with black baked enamel finish

Mounting Adjustable mounting brackets accept 1 1/2" "C" channel mounting bars • Indy Tru-Lock grid ceiling bar hangers are supplied standard • For non-accessible ceilings add suffix "825" for 28" "C" channel mounting bars • 3/4" maximum ceiling thickness. Trim collar is available for thicker ceilings; consult factory

Lamp Shown with bi-pin base T-4.5 type ceramic metal halide lamp (by others) • Protective clear tempered glass lamp guard is standard

Labels and Listings UL/C-UL Listed for feed through and damp locations • I.B.E.W. Union made

Ordering Information Example: HDSQ74-70E-SATSF-825

| Model | Lamp Wattage | Ballast | Trim Options | Options |
|--------|----------------|--------------------------|---|---|
| HDSQ74 | 70 | E | SATSF | 825 |
| HDSQ74 | 20 39 70 | E-120/277V Electronic | Alzak® Satin Finish Options SATSF^ - Clear CGTSF^ - Champagne Gold BATSF^ - Black PATSF^ - Pewter WTTSF^ - Wheat BRTSF^ - Bronze Painted Finish Options WHTF - White Cone | PF - Painted Flange Only (white) ***F - Fuse and Fuse Holder (Where *** = voltage) †CP - Chicago Plenum Approval 825-28" "C" Channel Mounting Bars (pair) |

Dimensions

